

IP DECT Phone I-3000

Features:

- VoIP/DECT phone

DECT main features:

- GAP compatible
- Frequency: 1880 ~ 1900 MHz
- Register up to 3 handsets
- Supports 4 active handsets via 4 channels simultaneously
- Range around 50m (indoor) or 300m (outdoor)
- Voice Compression : 32K ADPCM
- Modulation : GFSK
- Carrier Spacing : 1.728MHz
- Intercom, call transfer between cordless handsets



Base Function:

- Intercom
- Caller name for VoIP
- Call Transfer
- Call Hold
- Call waiting tone
- Paging

Handset features : (UT-870 handset)

- LCD display
- Selectable ringer melody
- Hand free function
- Phonebook with 50 sets memory
- 20 Caller ID memories
- 20 dialed numbers review & redial

Network Interface:

- RJ-45x1,10/100BaseT

Call Control/Network Protocol:

- SIP(RFC3261)
- RTP/RTCP/UDP/TCP/IP
- DHCP/PPPoE/Static IP
- DNS/TFTP/HTTP/NAT(STUN)

Codec:

- G.711 A/u-law
- G.729
- iLBC

Voice Quality:

- VAD/CNG/G.168
- Adaptive jitter control
- Packet loss concealment

QoS:

- ToS
- Diff Serv



Uwin Technologies Co., Ltd.

2F. No.22. R&D RD. II, SBIP. Hsinchu, Taiwan

TEL:886-3-5788690 FAX:886-3-5788741

<http://www.uwin.tw>